

# UN38.3 Test Summary

The following product has been evaluated according to the 6th revised edition of the UN Manual of Tests and Criteria.  
We, LG Chem, Ltd., hereby certify that this battery meets the requirements of the regulation for transportation of lithium-ion cells, batteries and single cell batteries.

Manufacture's contact information	LG Chem, Ltd. 128 Yeoui-Daero, Yeongdeungpo-gu, SEOUL, 150-721, REPUBLIC OF KOREA Telephone : +86-10-7742-5427      E-mail : kkammy@lgchem.com      Website : <a href="http://www.lgchem.com">www.lgchem.com</a>		
Test Laboratory information	LG Chem, Ltd. / RESEARCH PARK 188 Munjiro, Yuseong-gu, Daejeon, 305-738, REPUBLIC OF KOREA Telephone : +82-10-3099-3724      E-mail : juhongpark@lgchem.com      Website : <a href="http://www.lgchem.com">www.lgchem.com</a>		
	LG Chem (Nanjing) I&E Materials Co., Ltd NO.17 Hengyi Road, Nanjing Economic & Technological Development Zone, Nanjing, Jiangsu, China Telephone : +86-025-85603000-8288      E-mail : xuyuannj@lgchem.com      Website : <a href="http://www.lgchem.com">www.lgchem.com</a>		
Description		List of Test Completed	
Test Report Number	190124-[UN38.3] EB-BG975AB	Test 1. Altitude Simulation	Pass
Date of test report	2019.01.24	Test 2. Thermal Test	Pass
Model name	EB-BG975AB	Test 3. Vibration	Pass
Type	Pouch (Lithium ion battery)	Test 4. Shock	Pass
Nominal voltage	3.85 V	Test 5. External Short Circuit	Pass
Capacity	15.4 Wh	Test 6. Impact or Crush	Pass
Weight	57.234 g	Test 7. Overcharge	Pass
Dimensions	91.90mmX48.20mmX5.61mm	Test 8. Forced Discharge	Pass

Approved By: Yuan Xu  
 Part Leader  
 Cyl NPI&CE lab part DQA Team  
 LG Chem, Ltd.  
 E-mail: xuyuannj@lgchem.com

