MSDS Report

Samples: Rechargeable Li-ion Battery GD1J6

Supplier Unit: SUNWODA ELECTRONIC CO., LTD

Supplier Address: No.2, Yihe Rd, Shilong Community, Shiyan Street, Baoan District, Shenzhen City, China

MSDS No.: MSDS2025051201

Release Date: May. 12, 2025



Material Safety Data Sheet

Section 1 – Chemical Product and Company Identification

Product Name: Rechargeable Li-ion Battery

Product Model: GD1J6

GPN: G823-00680-00

Manufacturer: SUNWODA ELECTRONIC CO., LTD

Address: No.2, Yihe Rd, Shilong Community, Shiyan Street, Baoan District, Shenzhen City, China

Post Code: 518108

Tel: 0755-29516888

Emergency Telephone: 0755-29516888

Fax: 0755-29516999

E-mail: zhangyuxia@sunwoda.com

Section 2 – Composition/Information on Ingredient

Component	CAS No.	EC No.	%/wt.
Cobalt lithium dioxide	12190-79-3	235-362-0	15-40
Ethyl propionate	105-37-3	203-291-4	15-40
Copper foil	7440-50-8	231-159-6	10-30
Aluminum foil	7429-90-5	231-072-3	10-30
Graphite	7782-42-5	231-955-3	7-25
Ethylene Carbonate	96-49-1	202-510-0	0-15
Propylene Carbonate	108-32-7	203-572-1	0-15
Lithium Hexafluorophosphate(1-)	21324-40-3	244-334-7	0-15
1,3-propanesultone	1120-71-4	214-317-9	0-1
Separator	9002-88-4	618-339-3	0-5

Section 3 –Hazards Identification

Health Hazards (Acute and Chronic)

These chemicals are contained in a sealed can .Risk of exposure occurs only if the battery is mechanically or electrically abused. Contact of electrolyte and extruded lithium with skin and eyes should be avoided.

Sign/Symptoms of Exposure

A shorted lithium battery can cause thermal and chemical burns upon contact with the skin. May be a reproductive hazard.

Section 4 – First Aid Measures

Eyes

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Skin

Remove contaminated clothes and rinse skin with plenty of water of shower for 15 minutes.

Get medical aid.

Inhalation

Remove from exposure and move to fresh air immediately. Use oxygen if available.

Ingestion

Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

Section 5 – Fire Fighting Measures

Flash Point: N/A

Auto-Ignition Temperature: N/A

Extinguishing Media: Dry powder, CO_2

Special Fire-Fighting Procedures: Self -contained breathing apparatus.

Unusual Fire and Explosion Hazards: Cell may vent when subjected to excessive heatexposing battery contents.

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 6 – Accidental Release Measures

Steps to be taken in case Material is Released of Spilled

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can.

The preferred response is to leave the area and allow the batteries to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

Waste Disposal Method

It is recommended to discharge the battery to the end, handing in the abandoned batteries to related department unified, dispose of the batteries in accordance with approved local, state, and federal requirements. Consult state environmental protection agency and/or federal EPA.

Section 7 –Handling and Storage

The batteries should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container.

Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.

Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change .Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

Other Precautions

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

Section 8 –Exposure Controls, Personal Protection

Respiratory Protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting batteries. Respiratory Protection is not necessary under conditions of normal use.

Ventilation

Not necessary under conditions of normal use.

Protective Gloves

Not necessary under conditions of normal use.

Other Protective Clothing or Equipment

Not necessary under conditions of normal use.

Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

Section 9 –Physical and Chemical Properties

Nominal Voltage:3.88V

Rated Capacity:5078mAh

Appearance characters: odorless, solid battery.

Section 10 –Stability and Reactivity

Stability

Stable

Conditions to Avoid

Heating, mechanical abuse and electrical abuse.

Hazardous Decomposition Products N/A.

Hazardous Polymerization N/A.

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalis, halogenated hydrocarbons.

Section 11 –Toxicological Information

Inhalation, skin contact and eye contact are possible when the battery is opened.

Exposure to internal contents, the corrosive fumes will be very irritating to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-fibrosis lung injury and membrane irritation.

Section 12 –Ecological Information

When promptly used or disposed the battery does not present environmental hazard. When disposed, keep away from water, rain and snow.

Section 13 –Disposal Considerations

APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARTION

If batteries are still fully charged or only partially discharged, they can be considered a reactive hazardous waste because of significant amount of not creation, or unconsumed lithium remaining in the spent battery. The batteries must be neutralized through an approved secondary treatment facility prior to disposal as a hazardous waste. Recycling of battery can be done in authorized facility, through licensed waste carrier.

Section 14 –Transport Information

General packaging requirement：			
1.The cells or batteries must be protected so as to prevent short circuits.			
2.The cells or batteries or equipment must be packed in suitable strong outer packaging.			
3.If batteries contained in equipment, equipment must be secured against movement within the outer packaging and be packed so as to prevent accidental activation.			
No.	**UN numbers & Proper Shipping Name,** if applicable		
（1）	UN 3480_LITHIUM ION BATTERIES		
（2）	UN 3481_LITHIUM ION BATTERIES PACKED WITH EQUIPMENT		
（3）	UN 3481_LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT		
（4）	/		
No.	**Hazard Class**	**Packing Group**	**Packaging requirement**
☒	**Air transportation, according to IATA-DGR 66 th Edition (Effective 1 January-31 December 2025**		
（1）	Class 9	Strong package	Packing Instructio 965, section IB
（2）	Not restricted	Strong package	Packing Instruction 966, section II
（3）	Not restricted	Strong package	Packing Instruction 967, section II
☒	**Maritime transportation, according to IMO IMDG Code (Edition 42-24)**		
（1）	Not restricted	Strong package	Packing as per sp 188;EmS No.:F-A,S-I;Not Marrine pollutant
（2）	Not restricted	Strong package	Packing as per sp 188;EmS No.:F-A,S-I;Not Marrine pollutant
（3）	Not restricted	Strong package	Packing as per sp 188;EmS No.:F-A,S-I;Not Marrine pollutant

地址：中国深圳市宝安区石岩街道石龙社区颐和路 2 号
Address: No.2,Yihe Rd,Shilong Community,Shiyan Street,Baoan District,Shenzhen City,China
TEL：86-755-29516888 FAX：86-755-29516999

☒	**Road transportation, according to ADR-2025**		
（1）	Not restricted	Strong package	Packing as per sp18
（2）	Not restricted	Strong package	Packing as per sp18
（3）	Not restricted	Strong package	Packing as per sp18
□	**Railway transportation, according to RID-2025**		

Transport Fashion: By air or sea or by road

Section 15 –Regulatory Information

Law Information

《Dangerous Goods Regulation》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods》

《Occupational Safety and Health Act》(OSHA)

《Toxic Substances Control Act》(TSCA)

《Consumer Product Safety Act》(CPSA)

《Federal Environmental Pollution Control Act》(FEPCA)

《The Oil Pollution Act》(OPA)

《Superfund Amendments and Reauthorization Act Title III (302/311/312/313)》(SARA)

《Resource Conservation and Recovery Act》(RCRA)

《Safety Drinking Water Act》(CWA)

《California Proposition 65》

《Code of Federal Regulations》(CFR)

In accordance with all Federal, State and Local laws.

Section 16 –Additional Information

The above information is based on the date of which we are aware and is believed to be correct as of data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material of his particular purpose.